


QUICKDR@W® Demarcation Unit

Prysmian Part Number: See below



The QUICKDR@W Demarcation Unit enables up to two QUICKDR@W cable Lead In Assemblies to be terminated on the outside wall of a building. It provides a connection on the external wall for test and maintenance access. Patch-cords can then be passed, fully bend managed, through the wall into the building for connection to active FTTH equipment. The unit is sealed to prevent the ingress of moisture to IP55.

Features and Benefits

- Manufactured from fire resistant material to UL94-V0.
- Up to two QUICKDR@W cable Lead In Assemblies can be accommodated.
- Removable cover for easy access.
- The cover is fitted with an integral seal to prevent the ingress of moisture.
- A quick set resin is used to seal the cables into the unit.
- Sealed to IP55.
- Fitted with tamperproof screws for enhanced security.
- Accommodates up to two simplex SC type adapters or 2 duplex LC adapters to provide an external access point for testing and maintenance.
- Patch-cords are positively managed to a 30mm bend radius when they are passed through the wall.

Kit Contents

- 1 x CLI Base
- 1 x CLI Cover with Seal
- 6 x Security Screws
- Adapters (as per version ordered)
- Wall Fixings
- Installation Instructions

Additional Items

- Sealing Resin

Installation Tools

- Security Screw Driver

Part Numbers

Demarcation Unit: -

- XCPSC01137 – 1 x SC/APC simplex
- XCPSC01138 – 2 x SC/APC simplex
- XCPSC01139 – 1 x LC/APC duplex
- XCPSC01140 – 2 x LC/APC duplex

Technical Data

- Number of cable ports: 2
- Maximum cable diameter (mm): 7mm
- Required space envelope (mm): (L) 275 x (W) 60 x (D) 37
- Operating temperature: -20°C to + 60°C (5 to 95% RH)
- Material : FR ABS – Colour Dark Grey RAL 7030
- Sealing: IP 55

Logistics

- Packing Dimensions (mm): (l) 300 x (w) 100 x (d) 60
- Packed Weight (kg): 0.170
- Net weight (kg): 0.200
- Installation Instructions included

Additional Items

Sealing Resin

Used to provide a water and gas block at the cable entry. The resin pack fits into a standard single tube sealant gun (not supplied). One pack contains sufficient resin to seal in excess of 20 Demarcation Units, and is supplied with 2 application nozzles. The resin is re-usable such that the units can be sealed on different days.



Prysmian Part No. – XKTSC00094

Installation Tools

Security Screw Driver

The Security Screw Driver is used for installation / re-entering of the Quickdraw Demarcation Unit.



Prysmian Part No. – XCPSC00099

Please contact your local sales office listed on www.prysmiangroup.com

© Prysmian Group 2012, All Rights Reserved.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed correct at the time of issue. Prysmian Group reserves the right to amend this specification without notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.